

## HO5RN-F: 60°C, 500 Volt Neoprene Jacketed Flexible Cord 60°C Rubber Jacketed Harmonized Cable



### Application:

HO5RN-F Harmonized, 60°C, Neoprene jacketed, flexible cordage has been designed for medium mechanical load on hand tools, appliances, computers, medical devices, heaters, cooking/baking/frying equipment, mobile homes and any type of medium duty electrical/electronic equipment that has been designed for use outside of North America. Note: This product should not come in direct contact with high temperature components.

### Technical Information:

<b>Design:</b>	Finely stranded copper conductors; Rubber insulation;Talc; Neoprene jacket
<b>Bend Radius for Installation:</b>	15 x cable diameter
<b>Temperature Rating:</b>	-25°C to +60°C
<b>Voltage Rating:</b>	300/500 Volts
<b>Color Code:</b>	Blue, Brown, Green/Yellow
<b>Jacket Colors Available:</b>	Black
<b>Approvals:</b>	HAR; Conforms to CE Low Voltage Directive Conforms to VDE 0282 Part 4/HD 22.1, S2, IEC 245.4, 228, 245, 304, 3332-1; BS 6500 and 6360

CS Part No.	Conductors Size	Stranding	App. Diameter Min-Max (mm)	Approx. Weight lbs/mft	Cord Specifications
IC-0302008	2 x 0.75mm <sup>2</sup>	24 x 0.21mm	5.7 - 7.2	37	HO5RN-F
IC-0303008	3 x 0.75mm <sup>2</sup>	24 x 0.21mm	6.5 - 7.8	47	HO5RN-F
IC-0302010	2 x 1.0mm <sup>2</sup>	32 x 0.21mm	6.4 - 7.9	44	HO5RN-F
IC-0303010	3 x 1.0mm <sup>2</sup>	32 x 0.21mm	7.0 - 8.4	54	HO5RN-F